

ASTM A 193 Gr.B8T STEEL

CLASS 1

BOLTING MATERIAL FOR LOW TEMPERATURE SERVICE

ASTM A193 Gr.B8T Class 1 is a titanium stabilized austenitic stainless steel with good general corrosion resistance. It has excellent resistance to intergranular corrosion after exposure to temperatures in the chromiumcarbide solution treated and strain hardened precipitation, range of 800 – 1500°F (427 – 816°C). The alloy resists oxidation to 1500°F (816°C) and has higher creep and stress rupture properties than alloys 304 and 304L. It also possesses good low temperature toughness. ASTM A193 Gr.B8T Class 1 cannot be hardened by heat treatment, only by cold working. It can be easily welded and processed by standard shop fabrication practices.

Chemical Properties

С	Si	Mn	P	S	Cr	Ni
0.08 Max	1.00 Max	2.00 Max	0.045 Max	0.030 Max	18.0-20.0	8.0-11.0

Mechanical Properties

Yeild strength	Tensile strength	Elongation	Reduction	Hardness
Min 0.2% Mpa	Min Mpa	Min %	Min %	HRB Max
205	515	30	50	96

Heat Treatment

Carbide Solution Treated

Equivalent Designation

UNS \$32100 Gost 08X18H10T Din X6CrNiTi18-10 Werkstoff.No. 1.4541 AFNOR X6CrNiTi18-10 BS 321 S 12

CUSTOMER ASSISTANCE : customer@TorqBolt.com

Email:info@TorqBolt.com Web: www.TorqBolt.com