

HARDNESS CONVERSION TABLE HB-HRC-Rm

HB	HV	HRC	HRB	Rm	HB	HV	HRC	HRB	Rm
124	-	-	71.00	420	232	244.8	21.10	100	765
126	-	-	72.00	430	236	249.0	21.90	-	770
128	-	-	73.00	-	240	253.2	22.60	101	780
130	-	-	-	440	244	257.4	23.40	102	800
132	-	-	74.00	450	248	261.6	24.00	-	810
134	-	-	75.00	-	252	265.9	24.70	103	820
136	-	-	76.00	460	256	270.1	25.40	-	830
138	-	-	-	-	260	274.3	26.10	104	850
140	-	-	77.00	470	264	278.5	26.80	-	860
142	-	-	78.00	480	268	282.7	27.40	105	880
144	-	-	-	-	272	287.0	27.90	-	890
146	-	-	79.00	490	276	291.2	28.60	106	900
148	-	-	80.00	500	280	295.4	29.10	-	910
150	-	-	81.00	-	284	299.6	29.60	107	930
152	-	-	-	510	288	303.8	30.20	-	940
154	-	-	82.00	520	292	308.1	30.70	-	950
156	-	-	-	-	296	312.3	31.30	108	970
158	-	-	83.00	530	300	316.5	31.80	-	980
160	-	-	-	540	304	320.7	32.30	-	990
162	-	-	84.00	-	308	324.9	32.80	109	1010
164	-	-	-	550	312	329.2	33.30	-	1020
166	-	-	85.00	560	316	333.4	33.80	-	1030
168	-	-	-	-	320	337.6	34.30	110	1050
170	-	-	86.00	570	324	341.8	34.70	-	1060
172	-	-	-	-	328	346.0	35.10	-	1070
174	-	-	87.00	580	332	350.3	35.60	-	1090
176	185.7	-	-	590	336	354.5	36.10	-	1100
178	187.8	-	88.00	-	340	358.7	35.50	-	1120
180	189.9	-	-	600	344	362.9	36.90	-	1130
182	192.0	-	89.00	610	348	367.1	37.30	-	1140
184	194.1	-	-	-	352	371.4	37.70	-	1160
186	196.2	-	90.00	620	356	375.6	38.10	-	1170
188	198.3	-	-	630	360	379.8	38.50	-	1190
190	200.5	-	91.00	-	364	384.0	38.90	-	1200
192	202.6	-	-	640	368	388.2	39.20	-	1210
194	204.7	-	92.00	650	372	392.5	39.60	-	1230
196	206.8	-	-	-	376	396.7	39.90	-	1240
198	208.9	-	93.00	660	380	400.9	40.40	-	1260
200	211.0	-	-	-	384	405.1	40.70	-	1270
202	213.1	-	94.00	670	388	409.3	41.10	-	1280
204	215.2	-	-	680	392	413.6	41.40	-	1290
206	217.3	15.00	-	-	396	417.8	41.80	-	1310
208	219.4	15.40	95.00	690	400	422.0	42.10	-	1320
210	221.6	15.90	-	700	404	426.2	42.50	-	1330
212	223.7	16.40	96.00	-	408	430.4	42.80	-	1350
214	225.8	16.90	-	710	412	434.7	43.20	-	1370
216	227.9	17.60	-	720	416	438.9	43.60	-	1380
218	230.0	18.10	97.00	-	420	443.1	43.90	-	1390
220	232.1	18.50	-	730	424	447.3	44.20	-	1410
222	234.2	19.00	98.00	-	428	451.5	44.50	-	1430
224	236.3	19.40	-	740	432	455.8	44.90	-	1440
226	238.4	19.80	-	750	436	460.0	45.20	-	1460
228	240.5	20.30	99.00	-	440	464.2	45.50	-	1470
230	242.7	20.70	-	760	444	468.4	45.80	-	1490